



TLBE

HYDRAULIC MULCHING HEAD

(for mini excavators)



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLBE

HYDRAULIC MULCHING HEAD

(for mini excavators)



STANDARD EQUIPMENT

- attachment saddle (20/30kg)
- hydraulic gear motor group 2
- anti-cavitation valve
- belt transmission
- rotor with smooth hammers
- internal counter-elements
- front protection with double row of chains and rubber
- rear rubber protection
- pair of skids
- rear height-adjustable roller with scraper
- special powder or liquid painting (primer and enamel)

The TLBE mulching head is ideal for the shredding of grass, reeds and bushes up to a maximum of 5 cm in diameter, near ditches, embankments and on all steep slopes. Fits mini excavators weighing from 1.8t to 5t.

Mod.									
	B	L	* Kg	(g/min.)	L/1 * *	Press. BAR	Kit	∅	D. Rotor
TLBE-50	650	540	180	2300	22/30	200	6	-	108
TLBE-70	850	740	200	2300	35/45	250	-	7	108
TLBE-90	1050	940	220	2300	40/45	250	-	9	108
TLBE-100	1150	1040	230	2300	45/60	250	-	10	108
TLBE-110	1250	1140	250	2300	45/60	250	-	11	108
TLBE-120	1350	1240	270	2300	45/60	250	-	12	108

* The data shown in the table are indicative, the weight refers to the mulching head without saddle and the litres are those required by the head for its operation.

ACCESSORIES ON REQUEST

1. Oscillating attachment (40kg)
2. Surcharge valve block with flow and pressure regulator
3. Surcharge motor group 3
4. Saddle fixing pins
5. There is an additional cost for customising of the saddle



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)