



TLBS

MOVEABLE FLAIL

(light type)



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLBS

MOVEABLE FLAIL

(light type)



STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- stabiliser foot
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with smooth hammers
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- double acting piston for lateral displacement
- special powder or liquid painting (primer and enamel)


The TLBS Flail is a piece of equipment used for the shredding of grass and small shoots. It has a three-point hitch and can be applied to crawler and wheeled tractors. The hydraulic displacement (max 30 cm) allows the use in a decentralised position for the processing of crops, plantations, orchards, etc.

Mod.				 (Hp-kw) *	 (g/min.)		 D. Rotor	
TLBS-120	1340/850/950	1240	300	20/30-15/22	540	12	108	2
TLBS-130	1440/850/950	1340	310	20/30-15/22	540	13	108	2
TLBS-140	1540/850/950	1440	320	20/30-15/22	540	14	108	3
TLBS-150	1640/850/950	1540	340	20/30-15/22	540	15	108	3
TLBS-160	1740/850/950	1640	350	20/30-15/22	540	16	108	3

* the horsepower shown are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

1. Pair of side skirts
2. Rear galvanised harpoons
3. Front rubber protection on the strips



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)