



TLC-S

MOVEABLE FLAIL
(heavy type)



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLC-S

MOVEABLE FLAIL

(heavy type)



STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with toothed hammers
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- rear hood opening for inspection
- double acting piston for lateral displacement
- special powder or liquid painting (primer and enamel)

The TLC-S flail is a tool used for the shredding of grass and branches, for the pruning of vineyards, orchards and olive groves. It has a three-point hitch and an openable hood that facilitates the inspection of the processed material and the state of wear of the machine. Adjustable displacement (max 30 cm) is guaranteed by a hydraulic cylinder transversally positioned between the booms which allows its use both in a normal position and in a decentralised position for plantation row work. It adapts to any tracked or wheeled tractor.

Mod.				 (Hp-kw) *	 (g/min.)		 D. Rotor	
TLC- S 140	1560/970/970	1440	480	40/45-29/33	540	10	160	3
TLC-S 150	1660/970/970	1540	500	45/50-33/37	540	10	160	3
TLC-S 160	1760/970/970	1640	530	50/55-37/40	540	11	160	4
TLC-S 180	1960/970/970	1840	580	55/60-40/44	540	12	160	4
TLC-S 200	2120/970/970	2000	610	60/65-44/48	540	13	160	4
TLC-S 220	2360/970/970	2240	630	65/70-48/51	540	15	160	4

* the horsepower shown are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

1. Pair of side skirts
2. Oversized hammer supports
Sizes 140-150
Sizes 160-220
3. Double lower attachment on the stand with levelling joint
4. Front rubber protection on the strips



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)