



TLE-FP

FORESTRY HYDRAULIC MULCHING HEAD
(for excavator)



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLE-FP

FORESTRY HYDRAULIC MULCHING HEAD

(for excavator)



STANDARD EQUIPMENT

- DOMEX sheet metal body
- inner counterframe with Hardox wear-resistant PLATE
- attachment saddle (70 kg)*
- saddle adjustment rail
- hydraulic piston engine with external drainage
- anti-cavitation valve
- belt transmission
- series of internal counter-elements
- forestry rotor with two-way retractable hammers
- front and rear protection with galvanised chains
- pair of skids with HARDOX wear-resistant sheet metal reinforcement
- support foot
- special powder or liquid painting (primer and enamel)

The TLE-FP forestry mulching head is ideal for the shredding of grass, reeds and bushes up to a maximum of 15/25cm in diameter near ditches, embankments and steeply sloping terrains, for uncultivated areas and woodlands. The TLE-FS mulching head is applicable to excavators with a weight of 20T.

Mod.									
	B	L	* Kg	(g/min.)	L/1' *	Press. BAR	Ø	D. Rotor	
TLE-FP 110	1510	1170	1000	2300	170/180	300	24	430	4
TLE-FP 150	1890	1550	1250	2300	170/180	300	30	430	4

* The data shown in the table are indicative, refer to the weight of the mulching head without saddle and the litres are those required by the shredding head for its operation.

ACCESSORIES ON REQUEST

1. Saddle fixing pins
2. There is an additional cost for customising of the saddle



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)