



# TLGA

## MOVEABLE FLAIL

(medium heavy type)



[www.lipa-srl.it](http://www.lipa-srl.it)  
[info@lipa-srl.it](mailto:info@lipa-srl.it)

65010 Spoltore (PE) - Italy  
Via Castellani (ang. Via Mare Adriatico)  
Tel. +39 085 4971431 Fax +39 085 4973170

# TLGA

## MOVEABLE FLAIL

(medium heavy type)



### STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- double stabiliser foot
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with smooth hammers
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- pair of side skids
- double acting piston for lateral movement with flow regulator
- double acting piston for angular inclination with D.E. lock valve with flow regulator
- levelling joint
- special powder or liquid painting (primer and enamel)

The TLGA flail is a piece of equipment used for the shredding of shrubs near ditches, banks and orchards. The TLGA equipment can work both sideways and as a common mulcher thanks to the booms that allow it greater versatility.

Mod.				 (Hp-kw) *	 (g/min.)	 D. Rotor		
<b>TLGA-140</b>	1560/1000/1800	1440	550	30/35-22/26	540	14	140	3
<b>TLGA-150</b>	1660/1000/1800	1540	570	35/40-26/29	540	15	140	3
<b>TLGA-160</b>	1760/1000/1800	1640	590	40/45-29/33	540	16	140	3
<b>TLGA-180</b>	1860/1000/1800	1740	610	40/45-29/33	540	20	140	4

\* the horsepower shown are indicative and express the power required by the flail for its operation.

### ACCESSORIES ON REQUEST

1. Surcharge single homokinetic cardan
2. Gearbox outside the mulcher
3. Double lower attachment on the stand
4. Rubber protection on strips

