

TLGS
MOVEABLE FLAIL
(medium heavy type)



www.lipa-srl.it info@lipa-srl.it 65010 Spoltore (PE) - Italy Via Castellani (ang. Via Mare Adriatico) **Tel. +39 085 4971431 Fax +39 085 4973170**







STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with smooth hammers
- belt transmission
- rear heightadjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- double acting piston for lateral displacement
- special powder or liquid painting (primer and enamel)

The TLGS Flail is a piece of equipment used for the shredding of grass and branches of vineyards and orchards. It has a three-point hitch and can be applied to crawler and wheeled tractors. The hydraulic displacement (max 40 cm) allows the work in a decentralised position in order to allow processing closer to the plantations, orchards, etc.

Mod.	(B/H/Z)		Kg	(Hp-kw) *	(g/min.)	2	Ø D. Rotor	
TLGS-130	1460/960/870	1340	435	25/30-18/22	540	13	140	3
TLGS-140	1560/960/870	1440	450	25/35-18/26	540	14	140	3
TLGS-150	1660/960/870	1540	470	30/35-22/26	540	15	140	3
TLGS-160	1760/960/870	1640	490	30/35-22/26	540	16	140	3
TLGS-180	1960/960/870	1840	540	35/40-26/29	540	18	140	4
TLGS-200	2120/960/870	2000	570	40/45-29/33	540	20	140	4

^{*} the horsepower shown are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

- 1. Pair of side skids
- 2. Inter-row disc Spring-loaded Hydraulic probe
- Double lower attachment on the stand with levelling joint
- **4.** Front rubber protection on the strips



