





www.lipa-srl.it info@lipa-srl.it 65010 Spoltore (PE) - Italy Via Castellani (ang. Via Mare Adriatico) **Tel. +39 085 4971431 Fax +39 085 4973170** 

## TLJL MOVEABLE FLAIL (heavy type)



## **STANDARD EQUIPMENT**

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- stabiliser foot
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with toothed hammers
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- rear hood opening for inspection
- oversized hammer supports
- double acting piston for lateral displacement
- special powder or liquid painting (primer and enamel)
- double lower attachment on the stand



The TLJL flail is a tool used for shredding and pruning in general, ideal for uncultivated areas. It has a three-point hitch and can be applied to crawler and wheeled tractors. The hydraulic displacement (max 45 cm) allows use of the flail in a decentralised position for crop row work.

Mod.	(BHHZ)		() Kg	(Hp-kw) *	(g/min.)	X	Ø D. Rotor	
TLJL-200	2160/920/970	2000	850	60-44	540/1000	13	180	5
TLJL-220	2400/920/970	2240	900	70-52	540/1000	15	180	5
TLJL-250	2700/920/970	2540	1000	80-59	540/1000	17	180	5
TLJL-280	3000/920/970	2840	1100	100-73	540/1000	20	180	5

<sup>\*</sup> the horsepower shown are indicative and express the power required by the flail for its operation.

## **ACCESSORIES ON REQUEST**

- 1. Pair of side skids
- 2. Galvanised and rubber chains to replace the strips
- 3. Rubber protection on the strips





