

www.lipa-srl.it info@lipa-srl.it 65010 Spoltore (PE) - Italy Via Castellani (ang. Via Mare Adriatico) **Tel. +39 085 4971431 Fax +39 085 4973170**





STANDARD EQUIPMENT

- · three-point hitch
- rear rubber protection
- front protection with galvanised strips
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with toothed hammers
- belt transmission
- rear heightadjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- rear galvanised harpoons
- double acting piston for lateral displacement
- special powder or liquid painting (primer and enamel)





The TLSP flail is a tool used for the shredding of grass and branches, for the pruning of vineyards, orchards and olive groves. It has a three-point hitch and can be applied to crawler and wheeled tractors. The TLSP flail is characterised by hydraulic displacement (max 40 cm) that allows it to be used in a decentralised position for crop row tasks.

Mod.	(B/H/Z)		Kg	(Hp-kw) *	(5)	A	Ø D. Rotor	
TLSP-130	1460/960/970	1340	500	30/35-22/26	540	9	140	3
TLSP-140	1560/960/970	1440	520	30/35-22/26	540	10	140	3
TLSP-150	1660/960/970	1540	540	35/40-26/29	540	10	140	3
TLSP-160	1760/960/970	1640	570	35/40-26/29	540	11	140	4
TLSP-180	1960/960/970	1840	620	45/50-33/37	540	12	140	4
TLSP-200	2120/960/970	2000	640	45/50-33/37	540	13	140	4
TLSP-220	2360/960/970	2240	660	50/60-37/44	540	15	160	4

* the horsepower shown are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

- 1. Pair of side skids
- 2. Oversized hammer supports
 Sizes 130-150
 Sizes 160-220
- Surcharge steering rubber wheel kit
- Inter-row disc Spring-loaded Hydraulic probe
- Double lower attachment on the stand with levelling joint
- **6.** Front rubber protection on the strips

The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)

