



TLT-FL

FORESTRY MULCHER



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLT-FL

FORESTRY MULCHER



STANDARD EQUIPMENT










- DOMEX sheet metal body
- inner counterframe with Hardox wear-resistant PLATE
- three-point hitch
- gearbox with internal freewheel
- cardan shaft

cardan protection boot

- belt transmission
- skids with Hardox wear-resistant plate reinforcement
- series of internal counter-elements
- openable hood with double-acting pistons
- forestry rotor with one-way retractable hammers
- front and rear protection with galvanised chain
- pair of skids with HARDOX wear-resistant sheet metal reinforcement
- support feet
- special powder or liquid painting (primer and enamel)



The TLT-FL forestry mulcher is ideal for forestry in the mulching of bushes and undergrowth, light thinning. In agriculture, the mulcher is suitable for the tasks of clearing orchards, tidying the landscape, for intensive work with rear mounting and reversible guide.

Mod.			 Kg	 (Hp-kw) *	 (g/min.)			 D. Rotor	
TLT-FL 130	1290	1660	950	80-59	540/1000	21	30	340	5
TLT-FL 150	1480	1850	1020	90-66	540/1000	24	36	340	5
TLT-FL 170	1660	2030	1080	100-74	540/1000	27	39	340	5

* the horsepower shown are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

- 1. Manual lowering stand**
TLT-FL 130
TLT-FL 150
TLT-FL 170
- 2. Hydraulic lowering stand**
TLT-FL 130
TLT-FL 150
TLT-FL 170
- 3. Surcharge rotor with fixed hammers**
TLT-FL 130
TLT-FL 150
TLT-FL 170

