



TLBE-S

HYDRAULIC MULCHING HEAD

(for excavator)



Made in Italy

www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLBE-S

industrial line



The TLBE-S mulching head is ideal for the mulching of grass, reeds and bushes up to a maximum of 7/8 cm in diameter, near ditches, embankments and on all steep slopes. Fits excavators with weight from 5T.

STANDARD EQUIPMENT

- attachment saddle (25kg)
- saddle adjustment rail
- hydraulic gear motor group 3
- anti-cavitation valve
- belt transmission
- rotor with toothed hammers and oversized hammer supports*
- internal counterframe
- double series of counter-elements
- front protection with galvanised chains and rubber
- rear rubber protection
- pair of skids
- rear height-adjustable roller with scraper
- special powder or liquid painting (primer and enamel)



Mod.									
	B	L	Kg	(g/min.)	L/1* *	Press. BAR	rotor mm		
TLBE-S 90	1050	940	320	2300	45/55	220/250	7	140	3
TLBE-S 100	1150	1040	330	2300	50/60	220/250	7	140	3
TLBE-S 110	1250	1140	350	2300	60/70	220/250	8	140	3
TLBE-S 120	1350	1240	370	2300	60/70	220/250	8	140	3

* The data shown in the table are indicative, the weight refers to the mulching head without saddle and the litres are those required by the head for its operation

ACCESSORIES ON REQUEST

1. Oscillating attachment (50kg)
2. Saddle fixing pins
3. Surcharge valve block with flow and limiter regulator
4. Swivel unit
5. There is an additional cost for customising of the saddle

*Oversized hammer supports not provided for the TLBE-S 90

