



SMART PRO



TLBE-SF

SEMI-FORESTRY HYDRAULIC MULCHING HEAD
(for midi-excavators)



Made in Italy

www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLBE-SF

industrial line



The mulching head TLBE-SF is ideal for mulching grass, reeds and shrubs until a maximum of 7/8 cm of diameter, close to ditches, embankments and on all steep slopes. It fits excavators having a weight starting from 5 tonnes to 8 tonnes.

STANDARD EQUIPMENT

- mounting bracket (25 kg)
- saddle adjustment rail
- hydraulic gear motor group 3
- anticavitation valve
- belt drive
- rotor with bidirectional rollaway hammers
- internal counterframe
- double series of counter-elements
- front and rear protection with galvanized chains
- cover adjustment bracket
- pair of skids
- special powder or liquid painting (primer and enamel)



Mod.									
	B	L	Kg	(g/min.)	L/1 *	Press. BAR		rotor mm	
TLBE-SF 70	950	740	300	2300	45/55	220/250	12	160	3
TLBE-SF 90	1150	940	390	2300	50/60	220/250	16	160	3
TLBE-SF 110	1350	1140	440	2300	60/70	220/250	20	160	3

* The data shown in the table are indicative, the weight refers to the mulching head without saddle and the litres are those required by the head for its operation

ACCESSORIES ON REQUEST

1. Saddle fixing pins
2. Surcharge for valve block with flow and limiter regulator
3. Surcharge for pistons engine
4. Rotor with smooth hammers
5. There is an additional cost for the customization of the saddle

1



2



3



4



The technical data, illustrations and features are indicative and do not commit the manufacturer.