



TLBE

HYDRAULIC MULCHING HEAD

(for mini-excavators)



Made in Italy

www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170



The TLBE mulching head is ideal for the shredding of grass, reeds and bushes up to a maximum of 5 cm in diameter, near ditches, embankments and on all steep slopes. Fits mini excavators weighing from 1.8t to 5t.

STANDARD EQUIPMENT

- attachment saddle (20/30kg)
- hydraulic gear motor group 2
- anti-cavitation valve
- belt transmission
- rotor with smooth hammers
- internal counter-elements
- front protection with double row of chains and rubber
- rear rubber protection
- pair of skids
- rear height-adjustable roller with scraper
- special powder or liquid painting (primer and enamel)

Mod.									
	B	L	Kg	(g/min.)	L/1' *	Press. BAR	Kit	rotor mm	
TLBE-50	650	540	180	2300	22/30	200	6	-	108 2
TLBE-70	850	740	200	2300	35/45	250	-	7	108 2
TLBE-90	1050	940	220	2300	40/45	250	-	9	108 2
TLBE-100	1150	1040	230	2300	45/60	250	-	10	108 3
TLBE-110	1250	1140	250	2300	45/60	250	-	11	108 3
TLBE-120	1350	1240	270	2300	45/60	250	-	12	108 3

* The data shown in the table are indicative, the weight refers to the mulching head without saddle and the litres are those required by the head for its operation

ACCESSORIES ON REQUEST

1. Oscillating attachment (40kg)
2. Surcharge valve block with flow and pressure regulator
3. Surcharge motor group 3
4. Saddle fixing pins
5. There is an additional cost for customising of the saddle

