



TLC

FLAIL
(heavy line)



Made in Italy

www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLC


heavy line



The TLC flail is a tool used for the shredding of grass and branches, for the pruning of vineyards, orchards and olive groves. It has a three-point hitch and an openable hood that facilitates inspection. It adapts to any tracked or wheeled tractor.

STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- stabiliser foot
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with toothed hammers
- belt transmission
- rear height- adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- rear hood opening for inspection
- special powder or liquid painting (primer and enamel)

Mod.			 Kg	 (Hp-kw) *	 (g/min.)		 rotor mm	
TLC-120	1360/800/900	1240	400	30/35-22/26	540	8	160	3
TLC-130	1460/800/900	1340	420	35/40-26/29	540	9	160	3
TLC-140	1560/800/900	1440	450	40/45-29/33	540	10	160	3
TLC-150	1660/800/900	1540	460	45/50-33/37	540	10	160	3
TLC-160	1760/800/900	1640	490	50/55-37/40	540	11	160	4
TLC-180	1960/800/900	1840	530	55/60-40/44	540	12	160	4
TLC-200	2120/800/900	2000	580	60/65-44/48	540	13	160	4
TLC-220	2360/800/900	2240	630	65/70-48/51	540	15	160	4

* The horsepower shown in the table are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

1. Pair of side skids
2. Oversized hammer supports
3. Front rubber protection on the strips

