



TLE-FP

FORESTRY HYDRAULIC MULCHING HEAD

(for excavator)



Made in Italy

www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLE-FP

forestry line

for excavator



The TLE-FP forestry mulching head is ideal for the shredding of grass, reeds and bushes up to a maximum of 15/25cm in diameter near ditches, embankments and steeply sloping terrains, for uncultivated areas and woodlands. The TLE-FP mulching head is applicable to excavators with a weight of 20T.

STANDARD EQUIPMENT

- sheet metal body with high yield index
- inner counterframe with wear-resistant plate
- attachment saddle (70 kg)*
- saddle adjustment rail
- hydraulic piston engine with external drainage
- anti-cavitation valve
- belt transmission
- series of internal counter-elements
- forestry rotor with two-way retractable hammers
- front and rear protection with galvan sed chain
- pair of skids with wear-resistant sheetmetal reinforcement
- support foot
- special powder or liquid painting (primer and enamel)

Mod.									
	B	L	Kg	(g/min.)	L/1' *	Press. BAR	rotor mm		
TLE-FP 110	1510	1170	1000	2300	170/180	300	24	430	4
TLE-FP 150	1890	1550	1250	2300	170/180	300	30	430	4

* The data shown in the table are indicative, the weight refers to the mulching head without saddle and the litres are those required by the head for its operation

ACCESSORIES ON REQUEST

1. Saddle fixing pins
2. There is an additional cost for customising of the saddle

