



TLE-FS/FM

FORESTRY HYDRAULIC MULCHING HEAD

(for excavator)



Made in Italy

www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLE-FS/FM

forestry line

for excavator



The TLE-FS/FM mulching heads with retractable or fixed hammer are suitable for the shredding of prunings and branches up to a maximum of 15cm in diameter. The TLE-FS mulching head is applicable to excavators weighing between 6t and 8t. The TLE-FM shredding head is applicable to excavators weighing between 8t and 10t.

STANDARD EQUIPMENT

- sheet metal body with high yield index
- internal reinforcement in anti-wear sheetmetal
- attachment saddle (55 kg)*
- saddle adjustment rail
- hydraulic piston engine with external drainage
- anti-cavitation valve
- belt transmission
- series of internal counter-elements
- forestry rotor with two-way retractable hammers
- front protection with galvanised and rubber chain
- double front and rear chain protection
- pair of skids with anti-wear sheet metal reinforcement
- special powder or liquid painting (primer and enamel)



Mod.										
	(mm)		Kg	(g/min.)	L/1*	Press. BAR	rotor mm	rotor mm	rotor mm	rotor mm
light series										
TLE-FS 70	984x550x920	714	410	2300	60/70	220/250	12	370	23	350
TLE-FS 90	1147x550x920	877	490	2300	70/80	220/250	15	370	29	350
medium series										
TLE-FM 100	1314x550x920	1043	550	2300	80/90	220/250	18	370	33	370
TLE-FM 110	1477x550x920	1206	630	2300	90/100	220/250	21	370	39	370

* The data shown in the table are indicative, the weight refers to the mulching head without saddle and the litres are those required by the head for its operation

ACCESSORIES ON REQUEST

1. Saddle fixing pins
2. Rotor with fixed hammers (ax and sharp)
3. Flow regulator valve with solenoid valve
4. There is an additional cost for customising of the saddle

