



# TLR-P

**REVERSIBLE FLAIL**  
(heavy line)



Made in Italy

**[www.lipa-srl.it](http://www.lipa-srl.it)**  
**[info@lipa-srl.it](mailto:info@lipa-srl.it)**

65010 Spoltore (PE) - Italy  
Via Castellani (ang. Via Mare Adriatico)  
Tel. +39 085 4971431 Fax +39 085 4973170

# TLR-P

## heavy line



The TLR-P flail is a piece of equipment that is suitable for work in forestry, in pastures and large fields. It has a front and rear attachment with lateral displacement. This reversibility means being able to maximise its performance and allows a choice of processing according to requirements.

### STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised and rubber chains
- support feet
- gearbox with through shaft with internal double freewheel
- cardan shaft
- cardan protection boot
- rotor with toothed hammers
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- rear hood opening for inspection
- oversized hammer supports
- double lateral hydraulic displacement
- double lower attachment on the stand
- special powder or liquid painting (primer and enamel)



| Mod.             |  |  |  Kg |  (Hp-kw) * |  (g/min.) |  |  rotor mm |  |
|------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>TLR-P 200</b> | 2160/950/1100                                                                     | 2000                                                                              | 900                                                                                  | 60-44                                                                                         | 1000                                                                                         | 13                                                                                  | 180                                                                                          | 5                                                                                   |
| <b>TLR-P 250</b> | 2700/950/1100                                                                     | 2540                                                                              | 1100                                                                                 | 80-59                                                                                         | 1000                                                                                         | 17                                                                                  | 180                                                                                          | 5                                                                                   |
| <b>TLR-P 280</b> | 2960/950/1100                                                                     | 2800                                                                              | 1260                                                                                 | 100-73                                                                                        | 1000                                                                                         | 19                                                                                  | 180                                                                                          | 5                                                                                   |

\* The horsepower shown in the table are indicative and express the power required by the flail for its operation.

### ACCESSORIES ON REQUEST

1. Pair of side skids
2. Oversized roller Ø 250mm

