



TLS

MOVEABLE FLAIL
(heavy line)



Made in Italy

www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLS

heavy line




The TLS flail is a tool used for the shredding of grass and branches, for the pruning of vineyards, orchards and olive groves. It has a three-point hitch and can be applied to crawler and wheeled tractors. The TLS flail is characterised by transversal hydraulic displacement (max 40 cm) that allows it to be used in a decentralised position for crop row tasks.

STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with toothed hammers
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- rear galvanised harpoons
- double acting piston for lateral displacement
- special powder or liquid painting (primer and enamel)



Mod.			 Kg	 (Hp-kw) *	 (g/min.)		 rotor mm	
TLS-140	1560/970/970	1440	500	30/35-22/26	540	10	140	3
TLS-150	1660/970/970	1540	520	35/40-26/29	540	10	140	3
TLS-160	1760/970/970	1640	550	35/40-26/29	540	11	140	4
TLS-180	1960/970/970	1840	600	45/50-33/37	540	12	140	4
TLS-200	2120/970/970	2000	620	45/50-33/37	540	13	140	4
TLS-220	2360/970/970	2240	680	50/60-37/44	540	15	160	4

* The horsepower shown in the table are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

1. Pair of side skids
2. Oversized hammer supports
3. Surcharge steering rubber wheel kit
4. Double lower attachment on the stand
5. Front rubber protection on the strips



The technical data, illustrations and features are indicative and do not commit the manufacturer.