



TLT-FM-S

MOVEABLE MULTI-PURPOSE MULCHER
(medium line)



Made in Italy

www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLT-FM-S


multi-purpose line



The TLT-FM-S multi-purpose flail is an interchangeable piece of equipment used for professional shredding, in agriculture for the clearing of orchards, for tidying of the landscape, for heavy uses, use with rear assembly; in forestry for the mulching of brushwood, undergrowth and light thinning. It has an openable hood that facilitates reverse processing, increasing the ability to convey the processed material, increasing its work efficiency.

STANDARD EQUIPMENT

- sheet metal body with high yield index
- internal counterframe in wear-resistant sheet metal
- three-point hitch
- double lower attachment on the stand
- front protection with double row of galvanised chains
- support feet
- oversized gearbox with internal freewheel
- 3/4 Z6 cardan shaft suitable for 120/140 HP
- V80 cardan joint
- cardan protection boot
- belt transmission
- hydraulic lateral displacement
- series of internal counter-elements
- rotor with toothed hammers
- oversized hammer supports
- triple series of welded internal counter-elements
- front protection with galvanised and rubberchain
- double front and rear chain protection
- side skids with wear-resistant sheet reinforcement
- rear hood that can be opened with a roller of D. 170
- two double-acting pistons for hood opening
- special powder or liquid painting (primer and enamel)

Mod.			 Kg	 (Hp-kw) *	 (g/min.)		 rotor mm	
TLT-FM-S140	1710x1100x1300	1440	750	60-65	540	10	160	4
TLT-FM-S160	1910x1100x1300	1640	800	60-65	540	11	160	4
TLT-FM-S180	2110x1100x1300	1840	900	70-75	540	12	160	5
TLT-FM-S200	2270x1100x1300	2000	1000	80-85	540	13	180	5
TLT-FM-S220	2510x1100x1300	2240	1100	80-85	540	15	180	5

* The horsepower shown in the table are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

1. Rear galvanised harpoons
2. Rotor with smooth hammers



Hole Ø28.5

